

WBX180 CLEARVersion Number 1.0
Revision Date 03/20/2003Page 1 of 6
Print Date 11/10/2011**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**
2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE : Product Stewardship, (314) 771-1800

Emergency telephone number : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**

Product name : WBX180 CLEAR

Product code : FO00011837

Chemical Name : Mixture

CAS-No. : Mixture

Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

This product is a water based mixture with an ammonia odor. The mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. The product is not combustible, but it will burn if involved in a fire, releasing hydrocarbon products of combustion. Inhalation of the ammonia from this product may cause respiratory irritation, coughing, sore throat, and labored breathing.

POTENTIAL HEALTH EFFECTS**Routes of Exposure:** : Skin contact, Inhalation, Ingestion**Acute exposure**

Inhalation : Symptoms of breathing ammonia vapor concentrated from this product may include laryngitis, tracheitis, pulmonary edema, dyspnea, bronchospasms, and chest pains or pneumonitis. Symptoms are typically reversible.

Ingestion : May be harmful if swallowed.

Eyes : Liquid, aerosol, or vapors of this product are irritating and may cause tearing, reddening, and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

Skin : Skin contact may cause redness, irritation, and burns.

Chronic exposure : Refer to Section 11 for Toxicological Information.

MATERIAL SAFETY DATA SHEET

WBX180 CLEAR

Version Number 1.0
Revision Date 03/20/2003

Page 2 of 6
Print Date 11/10/2011

Medical Conditions : None known.
Aggravated by Exposure:

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of vapors or fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Seek medical attention if necessary.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : No data available.

Flammable Limits
Upper explosion limit : No data available.
Lower explosion limit : No data available.

Autoignition temperature : No data available.

Suitable extinguishing media : carbon dioxide (CO₂), water, foam, dry chemical.

Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

Unusual Fire/Explosion Hazards : Burning dry latex produces dense black smoke with the possibility of toxic vapors. Residual latex material contained in empty drums may decompose when burned producing toxic or irritating fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Ensure response personnel are properly protected (see section 8 for respiratory or other protection guidelines.) Use caution as floors may be slippery.

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal.

MATERIAL SAFETY DATA SHEET

WBX180 CLEAR

Version Number 1.0
Revision Date 03/20/2003

Page 3 of 6
Print Date 11/10/2011

7. HANDLING AND STORAGE

- Handling : Use only in area provided with appropriate exhaust ventilation. Prolonged heating may result in product degradation. Material may settle during storage. Careful mixing without introduction of air may be necessary before use.
- Storage : Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool place. Keep from freezing and temperature extremes.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Respiratory protection : A respirator is normally not required for routine handling of product in areas of good general ventilation and adequate local exhaust at processing equipment during routine operation. If using a cartridge respirator, an ammonia cartridge is required to filter out potential excess ammonia vapors.
- Eye/Face Protection : Safety glasses with side-shields. Wear goggles or face shield during operations that present a splash potential.
- Hand protection : Impervious gloves such as rubber or PVC
- Skin and body protection : Long sleeved shirts and long pants are adequate for normal handling. Where operations present a splash or spill potential, employees should wear chemically resistant clothing, boots, apron, gloves, and eye/face protection.
- Additional Protective Measures : Safety shoes
- General Hygiene Considerations : Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practices.
- Engineering measures : Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.

Exposure limit(s)

There are no known hazardous components above regulatory thresholds in this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

- | | | | |
|------------|--------------|------------------|-----------------------------|
| Form | : Liquid | Evaporation rate | : Slower than Butyl Acetate |
| Appearance | : Liquid | Specific Gravity | : Not determined |
| Color | : NO PIGMENT | Bulk density | : Not applicable. |

MATERIAL SAFETY DATA SHEET

WBX180 CLEAR

Version Number 1.0
Revision Date 03/20/2003

Page 4 of 6
Print Date 11/10/2011

Odor	: Slight ammonia	Vapor pressure	: Not established
Melting point/range	: Not applicable	Vapor density	: Heavier than air.
Boiling Point:	: Not applicable	pH	: Not determined
Water solubility	: Completely miscible		

10. STABILITY AND REACTIVITY

Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Extremes of temperature and direct sunlight. Keep from freezing.
Incompatible Materials	: Acids, metal salts, and solvents
Hazardous decomposition products	: Carbon dioxide (CO ₂), carbon monoxide (CO), oxides of nitrogen (NO _x), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

There are no known hazardous components above regulatory thresholds in this product.

12. ECOLOGICAL INFORMATION

Persistence and degradability	: No data available.
Environmental Toxicity	: No data available.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.

13. DISPOSAL CONSIDERATIONS

Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.

MATERIAL SAFETY DATA SHEET

WBX180 CLEAR

Version Number 1.0
Revision Date 03/20/2003

Page 5 of 6
Print Date 11/10/2011

IMO / IMDG : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : There are no known hazardous components above regulatory thresholds in this product.

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product
Ammonia, anhydrous	7664-41-7	0.0759	100 lbs	131,752 LB

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Canadian Regulations:

WHMIS Classification : Not controlled.

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed.

China IECS : Listed.

Europe EINECS : Not determined.

MATERIAL SAFETY DATA SHEET

WBX180 CLEAR

Version Number 1.0

Page 6 of 6

Revision Date 03/20/2003

Print Date 11/10/2011

Japan ENCS : Not determined.

Korea KECI : Not determined.

Philippines PICCS : Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.